



GMC Utilities Group Ltd, GMC House,
Millenium Business Park, Cappagh Road,
Ballycoolin, Dublin 11, Ireland.
Tel: +353 (0)1 864 9800
Email: info@gmcirl.com

TRAFFIC MANAGEMENT PLAN

PROJECT
3772881 IW CDS New Connection

LOCATION
Ard Fallen Cunningham Road Dalke Dublin




RECOMMENDED PRINT A3 | ISSUED : 25/02/2025 | REVISION - 00 | TMPs - 03 | DESIGNER - K.MUNSTER | DRAWN - K.MUNSTER | APPROVED - D.GOUGH




SITE SPECIFIC NOTES

1. Traffic Management to comply with Temporary Traffic Management 2019 publications Chapter 8 Traffic Signs Manual, Design Guidance & Operation Guidance.
2. Cunningham Road Closed.
3. On single carriageway roads of 50 km/h signs to be placed at 20m intervals. Additional signage may be used where deemed necessary. (Type A & B)
4. A Pedestrian walkway of 1.2m minimum to be maintained at all times, kerb ramps to be provided where required
5. Work Area to be barriered at all times.
6. TMP is based on information received at time of design, minor changes may be required on site. Major changes to site works will require revised TMP.
7. Below signage to be used where required.....




During darkness at unlit areas following a site risk assessment additional lighting to be installed

LEGEND:




Design Parameters for Level 1 (iii) (Single Carriageway 50 km/h)	
Design Parameters	Roadworks Type A (>12 Hours)
	Temporary Signs
Sign Size (mm)	600 Min
Sign Visibility (m)	50
Number of Signs	2
Cumulative Distance (m)	40
Distance between advance signs (m)	20
	Minimum Rate of Taper
Taper at Lane (m)	1 in 5
Taper at Hard Shoulder (m)	1 in 5
	Maximum Cone Spacing
Cone Height (mm)	750
At Taper (m)	3
Longitudinal (m)	3
	Maximum Lamp Spacing
At Taper (m)	6
Longitudinal (m)	6
	Safety Zone
Longitudinal (m)	5
Lateral (m)	0.5
	Lanes
Minimum Lane Width (m)	3 (2.5)
Two-way Roadway Width (m)	5

Note:
 A. 45 degree taper is required at active temporary traffic controlled layouts with cones at 1m centres.
 B. Cone spacing shown is the maximum permitted. Where geometry or any other site specific reason dictates the spacing shall be reduced accordingly.
 C. The optimum lane width for all classes of vehicles is 3.3m. This may be reduced to a minimum of 3.0m. Below this, HGVs and buses must be marshalled past the works. The absolute minimum lane width, if only cars and light vehicles are present, is 2.5m. Refer to Chapter 8, Paragraphs 8.4.3.1 to 8.4.3.3.




PEDESTRIAN WALKWAY OF 1.2m MINIMUM REQUIRED WHEN WORKS ARE IN THE FOOTPATH

SITE LOCATION MAP - Ard Fallen Cunningham Road Dalke Dublin



GMC Utilities Group Ltd, GMC House, Millenium Business Park, Cappagh Road, Ballycoolin, Dublin 11, Ireland.
 Tel: +353 (0)1 864 9800
 Email: info@gmcirl.com

Project ;	3772881 IW CDS New Connection
Location ;	Ard Fallen Cunningham Road Dalke Dublin
TM Method ;	Detailed Site Layout
Designer ; KM	Drawn ; KM Approved ; DG
Date ;	25/02/2025
Scale ;	NTS - USE FIGURED DIMENSIONS ONLY
TMP Guide Reference ;	TMP-001
Dwg Number ;	GMC-TMP-21321-REV00



GMC Utilities Group Ltd, GMC House,
Millenium Business Park, Cappagh Road,
Ballycoolin, Dublin 11, Ireland.
Tel: +353 (0)1 864 9800
Email: info@gmcirl.com

Project ;	3772881 IW CDS New Connection	
Location ;	Ard Fallen Cunningham Road Dalke Dublin	
TM Method ;	Diversion Route	
Designer ; KM	Drawn ; KM	Approved ; DG
Date ;	25/02/2025	
Scale ;	NTS - USE FIGURED DIMENSIONS ONLY	
TMP Guide Reference ;	TMP-003	
Dwg Number ;	GMC-TMP-21323-REV00	